



STERN-WILLIAMS CO., Inc.

PO. BOX 8004 • SHAWNEE MISSION, KANSAS 66208-0004
913-362-5635 • FAX 913-362-6689 • www.sternwilliams.com

OUTDOOR SHOWER /DRINKING FOUNTAIN SPECIFICATIONS

MODEL: 6600

TYPE: Drinking fountain with standard body and foot shower.

PEDESTAL: 6-5/8" diameter steel pipe with 1/8" wall.

ARM: 3/16" sheet steel arm projecting 20" from pedestal.

RECEPTOR: 18 gauge stainless steel with chrome plated brass drain plug.

BUBBLER: Chrome plated brass, locked to receptor with vandal resistant steel guard.

HEAD: Two (2) chrome plated brass. Vandal proof design with no exposed fasteners, non removable spray heads, 2.5 gpm flow rate, adjustable spray pattern with 1/8" allen wrench inserted through spray head orifice.

VALVE: Showers - two (2) chrome plated brass push button assemblies recessed in 1/2" steel plate. Pneumatically operated metering type. Metering cycle is adjustable from 5 seconds to 2 minutes. Drinking fountain – chrome plated brass push button assembly recessed in 1/2" steel plate with stream regulator.

MOUNTING: Surface. 12" diameter o.d. base support plate with four (4) holes.

WASTE: 1-1/4" schedule 40 PVC

SUPPLY: 1/2" reinforced vinyl tubing with 1/2" IPS hook-up and stainless steel fittings.

FINISH: Polyester powder coat.

COLOR: Blue. Optional colors: red, green, dark bronze, black, silver, sand, yellow, orange and white.

OPTIONS: -32 1/2" compression type with standard hose connection and vacuum breaker
-32-LK same as above with loose key
-85 valve box
-SMP-6 surface mounting plate
-SS stainless steel