

MODEL SF-5100 & SF-5110 STAINLESS STEEL WALL MOUNTED FOUNTAIN

Lustrous satin-finish stainless steel satisfies the criteria for cleanliness and easy care in medical centers and office buildings. Push button control located on front panel. Vandal resistant bottom plate and mounting plate are standard. Beveled front with or without back plate.

-FP are frost proof models. It is recommended that a dual check valve backflow prevention be installed in the waterline going to any FP fountain.

Model SF-5100 fountains come with a back plate.



FEATURES

- Mounting plate comes standard
- Access plates are vandal resistant and provide easy maintenance
- Push button valve on front
- Adjustable flow regulation
- 18 gauge brush finished stainless steel receptor with a vandal resistant chrome plated brass drain plug
- Stainless steel supply fittings connected to reinforced tubing
- In-line mesh screen strainer
- Attractive, protective stainless steel back plate
- Delivers 8.0 GPH of chilled water refreshment
- Supply complete with 1/2" IPS lock shield screwdriver stop
- 1-1/4" IPS waste pipes included with every fountain



(Shown top to bottom) Model SF-5100, Model SF-5110

ORDERING OPTIONS

Part Number

SF-5100-



Optional

BFCA-1: Cane Touch Apron

SF-5100-FP-



Optional

BFCA-1: Cane Touch Apron

SF-5110-



Optional

BFCA-1: Cane Touch Apron

SF-5110-FP-



Optional

BFCA-1: Cane Touch Apron

DIMENSIONS

All dimensions subject to manufacturing variance of plus or minus 1/4" (6 mm)

SF-5100 9-5/8"H x 19"W with 13" extension

SF-5110 7"H x 12"W with 12-1/2" extension

SF-5100



