

HL-1800 HL-1810, HL-1900, HL-1910, HL-2000, HL-2010, HL-2100, HL-2110

HILOW MOP SERVICE SINK

Made from the same high quality materials as all other Stern-Williams products, the HILOW series have the stainless steel cap cast into the threshold to protect the area of greatest use.

These units were developed when the need arose to more efficiently drain power-driven floor maintenance equipment. This efficient drop front styling allows the janitor to automatically dump waste water and reduces lifting of conventional cleaning equipment.

Stainless steel caps on all horizontal shoulders and tiling flange may be added to customize any sink to meet your specifications.



(Shown above) HL-1800

FEATURES

- Terrazzo is composed of pearl gray marble chips cast in white Portland cement which produces a compressive strength of 3000 PSI seven days after casting; then ground smooth, grouted and sealed to resist stains and moisture.
- Mop service basin shall meet requirements CSA B45.8-18 / IAPMO Z403-2018.
- The Hilow series shoulders have 12" high outside measurements, 9-3/4" high inside measurements, and are 1-1/4" wide and have a 6" drop front with stainless steel cap on threshold.
- Drain shall be stainless steel cast integral with removable stainless steel strainer, and sized for a gasket (QDC3XH000 included for 3" XHCI, plastic or steel pipe) or a caulked lead connection not less than 1" deep to a 3" pipe.
- Custom configurations available - Drain positions, overall sizes, integral stainless steel caps or tiling flanges options. Call for more information and pricing.

OPTIONAL COMPONENTS

- LB:** Lint Basket
- BP:** Back Panels - 24", 24"x36", 28", 30", 32", 26"
- V-70:** Vinyl Bumper Guards
- A-20:** Aluminum Bumper Guards
- T-10-VB:** Mop Sink Faucet - Rough Chrome
- T-15-VB:** Mop Sink Faucet - Polished Chrome
- T-35:** 30" Hose and Wall Bracket
- T-40:** Stainless Steel Mop Hanger
- QDC3SN000:** Quick Connect Gasket for 3" SV and NHCI Pipe
- QDC32000:** Quick Connect Gasket for 2" PVC and Iron Pipe

Pricing for optional components can be found at sternwilliams.com/pricing/



ORDERING OPTIONS

Part Number

HL-




Size

- 1800:** 24x24x12" (Stainless steel cap on threshold)
- 1900:** 32x32x12" (Stainless steel cap on threshold)
- 2000:** 36x36x12" (Stainless steel cap on threshold)
- 2100:** 36x24x12" (Stainless steel cap on threshold)
- 1810:** 24x24x12" (Stainless steel cap on all sides)
- 1910:** 32x32x12" (Stainless steel cap on all sides)
- 2010:** 36x36x12" (Stainless steel cap on all sides)
- 2110:** 36x24x12" (Stainless steel cap on all sides)

DIMENSIONS

All dimensions subject to manufacturing variance of plus or minus 1/4" (6 mm)

MODEL	SIZE	A	B	C	D
HL-1800	24x24x12	24	24	12	—
HL-1900	32x32x12	32	32	16	—
HL-2000	36x36x12	36	36	18	—
HL-2100	36x24x12	24	36	12	18
HL-1810	24x24x12	24	24	12	—
HL-1910	32x32x12	32	32	16	—
HL-2010	36x36x12	36	36	18	—
HL-2110	36x24x12	24	36	12	18



SPECS

Furnish and install Hilow mop service basin (mop sink) manufactured by Stern-Williams using white Portland cement. The terrazzo material shall have a compressive strength not less than 3000 PSI after full cure. Mop service basin shall meet requirements CSA B45.8-18 / IAPMO Z403-2018. All exposed terrazzo surfaces shall be ground smooth, grouted, and factory sealed to resist stains and moisture. Mop Service Basins shall have 6" drop with stainless steel cap for easy access for mop buckets and other service equipment. Mop service basins include a stainless drain body that is cast integral to the basin with a stainless steel strainer. Drain shall have inside connection to a 3" pipe sealed with factory provided gasket. Shall be made in the USA.

Stern-Williams offers optional integral casted stainless steel caps, tiling flanges or lint basket.