

SBC-1700, SBC-1702, SBC-1725, SBC-1750 **CORLOW MOP SINK**

Made from the same high quality materials as all other Stern-Williams products, the CORLOW series has the stainless steel cap cast into the threshold to protect the area of greatest use.

These units were developed when the need arose to more efficiently drain power-driven floor maintenance equipment. This efficient drop front styling allows the janitor to automatically dump waste water and reduces lifting of conventional cleaning equipment.



(Shown above) SBC-1700

FEATURES -

- Terrazzo is composed of pearl gray marble chips cast in white Portland cement which produces a compressive strength of 3000 PSI seven days after casting; then ground smooth, grouted and sealed to resist stains and moisture.
- Mop service basin shall meet requirements CSA B45.8-18 / IAPMO Z403-2018.
- The Corlow series shoulders have 12" high outside measurements, 9-3/4" high inside measurements, and are 1-1/4" wide and have a 6" drop front with stainless steel cap on threshold.
- Stern-Williams offers optional integral tiling flanges that extend 1" above the shoulder, model identified as SBC-1702.
- Drain shall be stainless steel cast integral with removable stainless steel strainer, and sized for a gasket (QDC3XH000 included for 3" XHCI, plastic or steel pipe) or a caulked lead connection not less than 1" deep to a 3" pipe.

NHCI Pipe

Custom configurations available - Drain positions, overall sizes, integral stainless steel caps or tiling flanges options. Call for more information and pricing.

OPTIONAL COMPONENTS

| ☐ S223-0003: Lint Basket |
|--|
| ☐ BP: Back Panels - 24", 24"x36", 28", 30", 32", 26" |
| ☐ V-70: Vinyl Bumper Guards |
| ☐ A-20: Aluminum Bumper Guards |
| ☐ T-10-VB: Mop Sink Faucet - Rough Chrome |
| ☐ T-15-VB: Mop Sink Faucet - Polished Chrome |
| ☐ T-35: 30" Hose and Wall Bracket |
| ☐ T-40: Stainless Steel Mop Hanger |
| ☐ QDC3SN000: Quick Connect Gasket for 3" SV and NHCI Pip |
| ☐ QDC32000: Quick Connect Gasket for 2" PVC and Iron Pipe |




Pricing for optional components can be found at sternwilliams.com/pricing/



ORDERING OPTIONS -

Part Number



Size

☐ **1700:** 24x24x12"


 \square 1702: 24x24x12" (with two tiling flanges)


☐ 1725: 32x32x12"☐ 1750: 36x36x12"

DIMENSIONS

All dimensions subject to manufacturing variance of plus or minus 1/4" (6 mm)

| MODEL | SIZE | Α | В | С | D | E |
|----------|----------|----|----|----|--------|--------|
| SBC-1700 | 24x24x12 | 24 | 24 | 12 | 15 | 12 ½ |
| SBC-1702 | 24x24x12 | 24 | 24 | 12 | 15 | 12 ½ |
| SBC-1725 | 32x32x12 | 32 | 32 | 12 | 23 1/4 | 12 1/4 |
| SBC-1750 | 36x36x12 | 36 | 36 | 12 | 26 | 13 ½ |





SPECS |

Furnish and corner install Cornaro mop service basin (mop sink) manufactured by Stern-Williams using white Portland cement. The terrazzo material shall have a compressive strength not less than 3000 PSI after full cure. Mop service basin shall meet requirements CSA B45.8-18 / IAPMO Z403-2018. All exposed terrazzo surfaces shall be ground smooth, grouted, and factory sealed to resist stains and moisture. Mop Service Basins shall have 6" drop with stainless steel cap for easy access for mop buckets and other service equipment. Mop service basins include a stainless drain body that is cast integral to the basin with a stainless steel strainer. Drain shall have inside connection to a 3" pipe sealed with factory provided gasket. Shall be made in the USA.

Stern-Williams offers optional integral casted stainless steel caps, tiling flanges or lint basket.