

MODEL 5380, 5480, 5780 & 5980

REFRIGERATED DRINKING FOUNTAINS

Our line of refrigerated drinking fountains offer 8.0 GPH of chilled water refreshment year-round. Each fountain is built to last the elements and may come with handicap accessible drinking fountains.

Model 5380 are the standard single pedestal fountain.

Model 5480 fountains are handicap accessible with a single pedestal drinking fountains

Model 5780 fountains are handicap accessible with a dual pedestal drinking fountains.

Model 5980 fountains are handicap and child accessible with a triple pedestal drinking fountains

FEATURES

- All steel heavy-duty construction with welded and ground joints for a clean and tidy appearance
- Stainless Steel (-SS) bodies available for harsh coastal environments
- Vandal resistant access plates for security and simple future maintenance
- Vandal resistant bubbler guard unique to Stern Williams Fountains assures years of service
- Water pressure range of 30-80 PSI.
- Anchor installed mounting plate comes standard, ground installed mounting plate available as an option for installation assistance (SMP-18).
- Recessed push button requires less than 5 lbs of force and is manufactured from chrome plated brass for reliability and long wear life with a water flow of 0.5 GPM.
- Simple flow adjustment without requiring the dismantling of the fountain
- Fountain Bowl is heavy duty 18 gauge stainless steel with brushed finish and vandal-resistant chrome plated brass strainer. A drain tool is included with each fountain.
- All flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q≤1 (AB100) standards.
- Delivers 8.0 GPH of outdoor chilled water refreshment
- In-line mesh screen Y strainer.
- ½” Inlet stop valve for simple future maintenance.
- 1 ¼” IPS waste pipes included on each fountain.
- Standard Woodland Green finish with optional colors available.



(Shown above) Model 5380



ORDERING OPTIONS

Part Number

5380-



Optional

- SS:** Stainless Steel Body Upgrade
- SMP-18:** Surface Mounting Plate

5480-



Optional

- SS:** Stainless Steel Body Upgrade
- SMP-18:** Surface Mounting Plate

5780-



Optional

- SS:** Stainless Steel Body Upgrade
- SMP-18:** Surface Mounting Plate

5980-



Optional

- SS:** Stainless Steel Body Upgrade
- SMP-18:** Surface Mounting Plate

*A maximum of 3 options may be added to a fountain.

DIMENSIONS

All dimensions subject to manufacturing variance of plus or minus 1/4" (6 mm)

5380 18" Dia. with 22-1/2" Dia. base plate / Standard, Single bubbler.

5480 18" Dia. with 22-1/2" Dia. base plate / Handicap accessible. Single bubbler

5780 18" Dia. with 22-1/2" Dia. base plate / Handicap accessible. Dual bubbler

5980 18" Dia. with 22-1/2" Dia. base plate / Handicap and child accessible. Triple bubbler.

SPEC

Furnish and install Stern-Williams Refrigerated Drinking Fountains (specify model # and options). Drinking fountain shall be carbon steel or 304 stainless steel and a powder coated finish. Fountain shall have chrome plated brass bubblers with vandal resistant bubbler guard. Water pressure range shall be 30-80 PSI. Fountains shall provide for simple flow adjustment without requiring dismantling of fountain with a water flow of 0.5 GPM. Joints must be welded and ground smooth. Push buttons shall require less than 5 lbs of force in compliance with ADA code. Fountains shall deliver 8.0 GPH of chilled water. Fountains shall be installed per manufacturers recommendations and instructions. Drinking fountain flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q_{≤1} (AB100) standards. Made in the USA.







