

## MODEL 7730 & 7925 TRIPLE FOUNTAIN AND BOTTLE FILLER STATIONS

Fill your bottle with a gravity-type spout and a recessed push-button with flow adjustment. Get your bottle filler as a barrier-free arm or as a pedestal with additional barrier-free drinking fountains.

Model 7730 includes a pedestal fountain with a fountain arm and a bottle filler arm.

Model 7925 includes a bottle filler pedestal with two fountain arms.

### FEATURES

- All steel heavy-duty construction with welded and ground joints for a clean and tidy appearance.
- Stainless Steel (-SS) bodies available for harsh coastal environments.
- Vandal resistant access plates for security and simple future maintenance.
- Vandal resistant bubbler guard unique to Stern Williams Fountains assures years of service .
- Water pressure range of 30-80 PSI.
- Anchor installed mounting plate comes standard, ground installed mounting plate available as an option for installation assistance (SMP-10).
- Recessed push button requires less than 5 lbs of force and is manufactured from chrome plated brass for reliability and long wear life with a water flow of 0.5 GPM.
- Simple flow adjustment without requiring the dismantling of the fountain.
- Fountain Bowl is heavy duty 18 gauge stainless steel with brushed finish and vandal-resistant chrome plated brass strainer. A drain tool is included with each fountain.
- All flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q≤1 (AB100) standards.
- In-line mesh screen Y strainer.
- ½” Inlet stop valve for simple future maintenance.
- 1 ¼” IPS waste pipes included on each fountain.
- Standard Woodland Green finish with optional colors available.



(Shown above) Model 7925



## ORDERING OPTIONS

Part Number

# 7730-



### Optional

- SS:** Stainless Steel Body Upgrade
- 31:** Chrome Plated Jug Filler
- 32:** RCP Hose bibb with VB
- 32-LK:** RCP Hose bibb with VB and Key
- 32-SC:** Self Closing Hose bibb with VB
- 32-VP:** Recessed Vandalproof Valve
- 35:** Recessed Compression Type
- 35-VP:** Recessed hose bibb with lock
- 36:** Push Button Jug Filler
- 37:** Foot Spray
- 38:** Shutdown/Drain Valve
- 40:** Commemorative Plaque
- 84:** Water Filter
- 85:** Valve Box
- 86:** Attached Metal Valve Box
- 87:** Surface Valve Box w/ Cover Plate
- 90:** Pet fountain
- 95:** Sand Trap
- 96:** Sand Strainer Plate
- 100:** Solar Light
- SMP-10:** Surface Mounting Plate

# 7925-



### Optional

- SS:** Stainless Steel Body Upgrade
- 31:** Chrome Plated Jug Filler
- 32:** RCP Hose bibb with VB
- 32-LK:** RCP Hose bibb with VB and Key
- 32-SC:** Self Closing Hose bibb with VB
- 32-VP:** Recessed Vandalproof Valve
- 35:** Recessed Compression Type
- 35-VP:** Recessed hose bibb with lock
- 36:** Push Button Jug Filler
- 37:** Foot Spray
- 38:** Shutdown/Drain Valve
- 40:** Commemorative Plaque
- 84:** Water Filter
- 85:** Valve Box
- 86:** Attached Metal Valve Box
- 87:** Surface Valve Box w/ Cover Plate
- 90:** Pet fountain
- 95:** Sand Trap
- 96:** Sand Strainer Plate
- 100:** Solar Light
- SMP-10:** Surface Mounting Plate

\*A maximum of 3 options may be added to a fountain.

## DIMENSIONS

These rough-in dimensions may vary 1/2" (13 mm) plus or minus

**7730** 54"H x 10-3/4"W x 50-3/4"L

**7925** 59"H x 10-3/4"W x 50-3/4"L

## SPEC

Furnish and install Stern-Williams Triple Pedestal Fountain and Bottle Filler Station (specify model # and options). Drinking fountain shall be carbon steel or 304 stainless steel and a powder coated finish. Fountain shall have chrome plated brass bubblers with vandal resistant bubbler guard. Water pressure range shall be 30-80 PSI. Fountains shall provide for simple flow adjustment without requiring dismantling of fountain with a water flow of 0.5 GPM. Welded anchor base shall be 1/2" thick. Joints must be welded and ground smooth. Push buttons shall require less than 5 lbs of force in compliance with ADA code. Fountains shall be installed per manufacturers recommendations and instructions. Drinking fountain flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q≤1 (AB100) standards. Made in the USA.



