

MODEL SPF-3100 & SPF-3101 SQUARE AGGREGATE FOUNTAIN

Square fountain in aggregate finish. Surface type with mounting plate welded to pedestal.

-FP are frost proof models. It is recommended that a dual check valve backflow prevention be installed in the waterline going to any FP fountain.

-FPS are sanifrost models which will not allow stored water to re-enter the bubbler.

FEATURES

- Vandal resistant access plates for security and simple future maintenance.
- Anchor installed mounting plate comes standard, ground installed mounting plate available as an option for installation assistance (SMP-12S).
- Simple flow adjustment without requiring the dismantling of the fountain.
- Recessed push button requires less than 5 lbs of force and is manufactured from chrome plated brass for reliability and long wear life with a water flow of 0.5 GPM.
- Water pressure range of 30-80 PSI.
- Fountain bowl is heavy duty 18 gauge stainless steel with brushed finish and vandal-resistant chrome plated brass strainer. A drain tool is included with each fountain.
- Aggregate bubbler guard with optional stainless steel bubbler guards (-42).
- Optional aggregate pet fountain (-94)
- Optional matching aggregate step (-60)
- All flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q≤1 (AB100) standards.
- In-line mesh screen Y strainer.
- ½" Inlet stop valve for simple future maintenance.
- 1 ¼" IPS waste pipes included on each fountain.



(00-Q) Quiet Creek
Light Etched



(00-C) Colorama
Light Etched



(01-Q) Quiet Creek
Medium Etched



(01-C) Colorama
Medium Etched

(Shown above) Model SPF-3101-C



ORDERING OPTIONS

Aggregate Color Options:

ADF-39

- ☐ **00:** Light Etched
- ☐ **01:** Medium Etched
- ☐ **C:** Colorama
- ☐ **Q:** Quiet Creek

Part Number

SPF-31XX-X-

SPF-31XX-X-FP-

SPF-31XX-X-FPS-

Optional

- ☐ **31:** Chrome Plated Self-closing Jug Filler
- ☐ **32:** RCP Hose bibb with VB
- ☐ **32-LK:** RCP Hose bibb with VB and Loose Key
- ☐ **33-VP:** Hose bibb with lock box
- ☐ **36:** Push Button Jug Filler
- ☐ **37:** Foot spray
- ☐ **38:** Shutdown/Drain Valve
- ☐ **40:** Commemorative plaque
- ☐ **65:** Matching step
- ☐ **75:** Chiller Unit with Aggregate Cover
- ☐ **84:** Water filter
- ☐ **85:** Valve Box
- ☐ **87:** Metal Valve Box
- ☐ **94:** Pet fountain
- ☐ **95:** Sand trap
- ☐ **96:** Sand strainer plate
- ☐ **SMP-12SQ:** Surface mounting plate

Optional

- ☐ **34-FP:** Frost Proof Jug Filler
- ☐ **38:** Shutdown/Drain Valve
- ☐ **40:** Commemorative plaque
- ☐ **65:** Matching step
- ☐ **75:** Chiller Unit with Aggregate Cover
- ☐ **85:** Valve Box (Recommended for -FP)
- ☐ **87:** Metal Valve Box
- ☐ **94-FP:** Frost proof
- ☐ **95:** Sand trap
- ☐ **96:** Sand strainer plate
- ☐ **SMP-12SQ:** Surface mounting plate

Optional

- ☐ **34-FPS:** Frost Proof Jug Filler
- ☐ **38:** Shutdown/Drain Valve
- ☐ **40:** Commemorative plaque
- ☐ **65:** Matching step
- ☐ **75:** Chiller Unit with Aggregate Cover
- ☐ **85:** Valve Box
- ☐ **87:** Metal Valve Box
- ☐ **94-FPS:** Frost proof
- ☐ **95:** Sand trap
- ☐ **96:** Sand strainer plate
- ☐ **SMP-12SQ:** Surface mounting plate

*A maximum of 3 options may be added to a fountain.

DIMENSIONS

All dimensions subject to manufacturing variance of plus or minus 1/4" (6 mm)

SPF-3100 36" H x 12"W x 12"L / Colorama, light etched

SPF-3100-94 36" H x 26"W x 12"L / Colorama, medium etched

SPEC

Furnish and install Stern-Williams Pedestal Drinking Fountain (specify model # and options). Drinking fountain shall be aggregate. Fountain shall have chrome plated brass bubblers with vandal resistant bubbler guard. Water pressure range shall be 30-80 PSI. Fountains shall provide for simple flow adjustment without requiring dismantling of fountain with a water flow of 0.5 GPM. Welded anchor base shall be 1/2" thick. Push buttons shall require less than 5 lbs of force in compliance with ADA code. Fountains shall be installed per manufacturers recommendations and instructions. Drinking fountain flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q≤1 (AB100) standards. Made in the USA.

SPF-3100



