

MODEL 6875 QUAD OUTDOOR SHOWER

One of our best complete line of outdoor showers with body sprays. Models 6875 and 6975 are versatile and great for resorts, playgrounds, and recreational outdoor areas. These outdoor showers are designed to comply to the roughest conditions.

Model includes four chrome plated brass shower heads. Vandal proof design with no exposed fasteners, non removable spray heads with an adjustable spray pattern with an 1/8" allen wrench inserted through spray head orifice.

FEATURES

- All steel heavy-duty construction with welded and ground joints for a clean and tidy appearance
- All exposed parts are recessed in welded steel plates
- Stainless Steel (-SS) bodies available for harsh coastal environments
- Vandal resistant access plates for security and simple future maintenance
- Optional mounting plates available for installation assistance
 - **SMP-6:** Surface mounting plate
 - **IBA-6:** In-ground mounting plate
- Recessed push button requires less than 5 lbs of force and is manufactured from chrome plated brass for reliability and long wear life
- ½" reinforced vinyl tubing with ½" IPS hook-ups and stainless steel supply fittings connected to reinforced tubing
- Water pressure range of 30-80 PSI
- Simple flow adjustment without dismantling of the shower tower with a water flow of 2.5 GPM
- Timer controlled shower heads are made from heavy duty materials with a preset running time of 60 seconds that can be adjusted from 0 to 60 seconds
- Shower head spray pattern is adjustable from stream to mist
- ½" inlet stop valve for simple future maintenance
- Standard Sky Blue finish with optional colors available
- Custom color orders are non-cancellable and non-returnable





ORDERING OPTIONS

Part Number

6875-



Optional

- SS:** Stainless Steel Body Upgrade
- 31:** Chrome Plated Jug Filler
- 32:** RCP Hose Bibb with VB
- 32-LK:** RCP Hose Bibb with VB and Key
- 32-SC:** Self Closing Hose Bibb with VB
- 32-VP:** Recessed Vandal Proof Valve
- 35:** Recessed Compression Type
- 35-VP:** Recessed Hose Bibb with Lock
- 38:** Shutdown/Drain Valve
- 40:** Commemorative Plaque
- 82:** Handwash Station
- 85:** Valve Box
- 87:** Metal Valve Box
- SMP-6:** Surface Mounting Plate
- IBA-6:** In-Ground Bury Adapter


DIMENSIONS

All dimensions subject to manufacturing variance of plus or minus 1/4" (6 mm)

6875 84"H x 6-5/8"Dia – Surface mount

SPEC

Furnish and install the Stern-Williams Quad Outdoor Shower (specify model color). Shower towers shall be carbon steel or 304 stainless steel and a powder coated finish. Shower heads shall be chrome plated brass with a water pressure range of 30-80 PSI. Shower heads shall include adjustable spray patterns and adjustable timing of 0-60 seconds. Shower towers shall provide simple flow adjustment without requiring dismantling of shower with a water flow of 2.5 GPM. Welded anchor base shall be 1/2" thick. Push buttons shall require less than 5 lbs of force. Shower towers shall be installed per manufacturers recommendations and instructions. Made in the USA.



NOTE: FOUR 9/16" O.D. MOUNTING BOLTS SPACED ON A 10" DIA @ 90°

12" DIA PLATE

