

MODEL 7325 SINGLE WATER BOTTLE FILLER STATION

Designed to be a convenient station to refill reusable water bottles with filtered water. Includes a brushed aluminum filler spout.

FEATURES

- All steel heavy-duty construction with welded and ground joints for a clean and tidy appearance.
- Stainless Steel (-SS) bodies available for harsh coastal environments.
- Vandal resistant access plates for security and simple future maintenance.
- Vandal resistant bubbler guard unique to Stern Williams Fountains assures years of service .
- Water pressure range of 30-80 PSI.
- Optional mounting plates available for installation assistance.
 - **SMP-6:** Surface mounting plate.
 - **IBA-6:** In-ground mounting plate.
- Recessed push button requires less than 5 lbs of force and is manufactured from chrome plated brass for reliability and long wear life with a water flow of 0.5 GPM.
- Simple flow adjustment without requiring the dismantling of the fountain.
- A drain tool is included with each fountain.
- All flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q≤1 (AB100) standards.
- In-line mesh screen Y strainer.
- Replaceable in-line water filter (S231-0251) is included and meets NSF standards.
- ½" Inlet stop valve for simple future maintenance.
- 1 ¼" IPS waste pipes included on each fountain.
- Standard Woodland Green finish with optional colors available.





ORDERING OPTIONS

Part Number

7325 -



Optional

- ☐ **SS:** Stainless Steel Body Upgrade
- ☐ **31:** Chrome Plated Jug Filler
- ☐ **32:** RCP Hose Bibb with VB
- ☐ **32-LK:** RCP Hose Bibb with VB and Key
- ☐ **32-SC:** Self Closing Hose Bibb with VB
- ☐ **32-VP:** Recessed Vandalproof Valve
- ☐ **35:** Recessed Compression Type
- ☐ **35-VP:** Recessed Hose Bibb with Lock
- ☐ **36:** Push Button Jug Filler
- ☐ **37:** Foot Spray
- ☐ **38:** Shutdown Drain Valve
- ☐ **40:** Commemorative Plaque
- ☐ **76:** Fountain Chiller
- ☐ **84:** Water Filter
- ☐ **85:** Ground Valve Box with Lid
- ☐ **86:** Attached Metal Valve Box
- ☐ **90:** Pet fountain
- ☐ **95:** Sand Trap
- ☐ **96:** Sand Strainer Plate
- ☐ **100:** Solar Light
- ☐ **SMP-6:** Surface Mounting Plate
- ☐ **IBA-6:** In-Ground Bury Adapter

*A maximum of 3 options may be added to a fountain.

DIMENSIONS

All dimensions subject to manufacturing variance of plus or minus 1/4" (6 mm)

7325 59"H x 6-5/8" Dia

SPEC

Furnish and install Stern-Williams Single Water Bottle Filler Station (specify model # and options). Drinking fountain shall be carbon steel or 304 stainless steel and a powder coated finish. Fountain shall have an aluminum brushed filler spout. Welded anchor base shall be 1/2" thick. Joints must be welded and ground smooth. Push buttons shall require less than 5 lbs of force in compliance with ADA code. Fountains shall be installed per manufacturers recommendations and instructions. Drinking fountain flow paths are lead-free with reinforced stainless-steel tubing that complies with NSF/ANSI/CAN 61: Q≤1 (AB100) standards. Made in the USA.

7325 -FP-



Optional

- ☐ **SS:** Stainless Steel Body Upgrade
- ☐ **34:** Frostproof Jug Filler
- ☐ **38:** Shutdown Drain Valve
- ☐ **40:** Commemorative Plaque
- ☐ **85:** Ground Valve Box with Lid
- ☐ **86:** Attached Metal Valve Box
- ☐ **90-FP:** Pet fountain
- ☐ **95:** Sand Trap
- ☐ **96:** Sand Strainer Plate
- ☐ **100:** Solar Light
- ☐ **SMP-6:** Surface Mounting Plate
- ☐ **IBA-6:** In-Ground Bury Adapter

